

DECLARATION OF PERFORMANCE



SNOW GUARD

Unique identification code of the product-type:

Orima® Snow guard, Orima® Grated snow guard

Name	Product code	Installation guide	Name	Product code	Installation guide
Oval tube 3,0 m	31010	LE DECRA, LE CEMBRIT, W-1, LE1 NEW, LE STANDARD, LE2, LE2 P, LE3, LE11, LE5, LE6, LE8, LE8D, LE8T, LE9, LE9W	Fastener 420 mm	30630	LE3, LE11, VLE3, VLE3H
Snow guard grating 2,43 m	32020	VLE2, VLE3, VLE5, VLE6, VLE7, VLE8	Fastener Metrotile	30650	LE5
Snow guard grating 1,23 m	32010		Fastener Standard	37370	LE STANDARD
Snow guard grating deep 2,46 m	32190	VLE2h, VLE3H	Fastener	30530	LE6, VLE5
Grating fastener	32140	VLE2, VLE2H, VLE3, VLE3H, VLE8, VLE7	Fastener brick	31050	LE8, VLE8
Fastener Decra	30500	LE DECRA	Fastener brick	31590	LE8
Fastener Cembrit	31850	LE CEMBRIT	Fastener, batten 32x100	30820	LE8D
Fastener W-1	W-1	W-1	Fastener Terreal DCL	31630	LE8T
Fastener 420 mm	30070	LE1 NEW	Fastener 350 mm	30120	LE9, LE9W, VLE7
Seam fastener	30090	LE2P	Fastener 400 mm	30130	LE9, VLE7
Lower supporter	30150		Fastener brick	32080	VLE6
Seam fastener set	35640	LE2, VLE2, VLE2H			

Intended use of building product

Horizontal barrier permanently fixed to the construction of pitched roofs, prevent accumulated snow from falling and moving, protect the coating of the roof and persons, constructions and equipment near the building..

Name of Manufacturer

Orima-Tuote Oy, Kankaantie 6, FI-16100 Orimattila
+358 3 872 100, www.orima.fi, myynti@orima.fi


Product testing Snow guards are tested according to SS 831367 static load. There is not a harmonised standard for snow guards and therefore cannot be CE marked.

Declared performance	Essential characteristics	Performance	Standard
	Mechanical strength	Static load 5 kN/m, 10 min	SS 831367

The performance of the product identified in this document is conformity with the declared performance above. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for and on behalf of the manufacturer by:

Orimattila, 20.6.2018


Mikko Ahonen, CEO