

Declaration of Performance no. CPR2023001

1. Product: profile sheet roofing and wall covering products
2. Product type identification (according to article 11 section 4): **Interlocking profile PROGANT 29/475**



3. Intended use:
Self-supporting profiled metal products for roofings, external cladding and internal lining.
4. Manufacturer: **AS Esco; 25 Aiandi Road, Viimsi 74001 Harju County, Estonia ; phone +372 6055 690 , www.weckman.ee; info@weckman.ee**
5. Authorized representative: Not applicable
6. The system or systems of assessment and verification of constancy of performance of the construction product, as set out in system 4
7. NPD
8. NPD
9. Declared performance

<i>Main features</i>	<i>Functionality</i>	<i>Harmonized technical specification</i>
Mechanical resistance:	Interlocking profile PROGANT 29/475 , thickness 0,50; 0,60 mm, class 1 – S280GD:S320GD+Z275 Side 1 : PE 25:50 µm; PURAL50 µm; PURAL MATT 50 µm; PVDF/HIARC 27 µm; GreenCoat Grown BT 26µm Side 2 2: Primer+epoxy 12 µm; PE 6-10 µm standard grey EVS-EN 508 Load Capacity: NPD	EN 1478:2006 (EVS 14782:2007)
Water permeability:	The product is waterproof	
Dimensional change:	According to EN 14782:2006	
Release of dangerous substances:	NPD	
External fire performance:	B _{ROOF(t1)} , B _{ROOF(t2)} , B _{ROOF(t3)}	
Reaction to fire:	A1	
Duration:	Same as mechanical strength	

10. The performance of the product as defined in points 1 and 2 shall be consistent with the declared performance referred to in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in section 4.

11. Signed by and on behalf of the manufacturer:

- Peep Siimon, CEO
- Viimsi, 12.05.2023